



# GROOVE

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	101P8HVAF0KW180	Design	1-strip	Moisture	EN13183	7%±2%
EAN Code	7393969043847	Grading	Dynamic	content		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Range	Kährs Spirit	Minimun Mean Density kg/m³ >800 kg/m³		
		Collection	Rugged Collection	Reaction To Fire	EN13501-1	Cfl-s1
		Resandable	1 time	Formaldehyde	EN717-1	E1
Dimensions	72 x 4 7/8 x 3/8"	Natural/Stained	Natural	Emission		
Weight per Package	37 lbs	Joint	Woodloc®	Content PCP	CEN/TR14823	3 ≤ 5 x 10-6n
Area per Package	19.4 sqft	Floor heating	Yes	Breaking	EN1533	NPD
Area per pallet (m²)	0 sqft		20 years	Strength N/mm²		
Package info	Packages may contain start and stop boards.	Wear-layer material	Hardwood	Thermal	EN12664	0,14 W/mK
		Core material	HDF	Conductivity		
DETAIL DESCRIPTION			3/8"	Thermal Resistance R-Value		.07 (m2K/W)
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be		Installation method	Floating, Glue-Down	Biological Durability	EN350-2	Class 1
		Installation method	Floating, Glue-Down	CARB2		Compliant

### COLOR CHANGE

Changes to golden brown.

present in all sizes and numbers.

## Other products in this collection







Groove

Trench Crater

#### **CERTIFICATES**







#### **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.