

Model: AC4 ENDLESS 1L LONG ISLAND

Codes: 100199485 - L167012875

Group: G-210

Format: 24,4X126,1

Thickness: 8 mm



## COMPOSITION
















|         | Size | Material         | Type of material                                       |
|---------|------|------------------|--|
| Layer 1 | 0.2  | Melamine         | Aminoplastic thermosetting resins                      |
| Layer 2 | 0.2  | Decorative paper |  |
| Layer 3 | 8    | HDF              | High-density Fiber Board and water-repellent glues     |
| Layer 4 |      | Backside         | Sheets of kraft paper impregnated with phenolic resins |

## CERTIFICATIONS

Carb certification

CARB: Phase II compliant

## FEATURES

-  Imitates the surface of wood
-  Beveled cut on the long sides of the board in order to create a continuity effect
-  5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Format where only one board has been used to finish the entire base surface
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  Abrasion-resistance level as per Standard UNE-EN 13329
-  Boards that have continuity between them, thus achieving the optical effect of much longer formats
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  32. General commercial

### DIMENSIONAL FEATURES

|  |  |              |
|--|--|--------------|
| Difference in height among items                               | ≤0.15 mm   | EN 13329*    |
| Dimensional variations related to changes in relative moisture | ≤0.90 mm   | EN 13329*    |
| Flatness of item (f)   | fw,Cóncavo≤0.50% fw,Convexo≤1%/fl,Cóncavo≤0.15% fl,Convexo≤0.20% | EN 13329*    |
| Item thickness   | ≤0.50 mm   | EN 13329*    |
| Joint between items  | ≤0.20 mm   | EN 13329*    |
| Length of face   | ≤0.50 mm   | EN 13329*    |
| Squareness of the item (q)                                     | ≤0.20 mm   | EN 13329*    |
| Straightness of face   | ≤0.30 mm/m   | EN 13329*    |
| Uv light fastness  | ≥4   | EN 438-2,16* |
| Width of face  | ≤0.20 mm   | EN 13329*    |

### LABORATORY TESTS

|   |                                   |                    |
|---|-----------------------------------|--------------------|
| Castor chair effect   | No damage                         | EN 425*            |
| Critical radiant flux   | Cfl                               | EN ISO 9239-1*     |
| Curvature   | 0.06 mm                           |                    |
| Density of the board  | 925 ±5 KG/M3                      | UNE EN 323*        |
| Dimensional stability   | 0.03%                             | EN 434:1994*       |
| Evaluation of propensity to accumulation of electrostatic charges | 1.2 kV                            | ISO 1815*          |
| Fire resistance   | Efl-s1                            | EN 13501*          |
| Formaldehyde emissions  | E1                                | EN 717*            |
| Furniture leg effect  | No damage                         | EN 424*            |
| Heat resistance   | R=0.057 m2 K/W                    | ISO 8302*          |
| Impact resistance   | IC2                               | EN 13329*          |
| Resistance to abrasion  | AC4                               | UNE EN 13329:2000* |
| Resistance to cigarette burns                                     | 4                                 | EN 438*            |
| Resistance to staining  | Grado 5 (G 1 y 2) y Grado 4 (G 3) | EN 438*            |
| Slip resistance (cls)   | Clase 2                           | EN 12633*          |
| Slip resistance (dcof)  | Class DS:≥0.30                    | EN 13893*          |
| Smoke density (burning)   | s1                                | EN 13501-1*        |
| Swelling in thickness   | ≤18%                              | ASTM D 1037*       |
| Swelling in thickness   | ≤18%                              | UNE-EN 13329:2000* |

### PACKING

|               |                 |  |
|---------------|-----------------|--|
| Base unit     | PIECES          |  |
| Boxes         | 2.4615 M2/BOX   |  |
| Gross weight  | 7.5207 KG/M2    |  |
| Net weight    | 7.2249 KG/M2    |  |
| Pallets       | 73.8442 M2/PAL  |  |
| Sale unit     | M2              |  |
| Square meters | 1 M2            |  |
| Units         | 0.3077 M2/PIECE |  |

### SPECIAL PIECES

| SAP       | KEA        | Description                              | Group | Boxes    | Pallet      | Units       | SKU | Basic Unit | Net Weight | Gross weight |
|-----------|------------|--|-------|----------|-------------|-------------|-----|------------|------------|--------------|
| 100153880 | L167012513 | IGUALACION ENDLESS 1L LONG ISLAND 4X270  | G-155 | 20 ST/CS | 1000 ST/PAL | 9.26 ST/M2  | ST  | ST         | 0.77 KG/ST | 0.8 KG/ST    |
| 100176700 | L167012692 | MAMPERLAN AC4 ENDLESS 1L LONG ISLAND 120 | G-163 | 2 ST/CS  | 200 ST/PAL  | 11.9 ST/M2  | ST  | ST         | 1.58 KG/ST | 1.64 KG/ST   |
| 100153887 | L167012517 | TRANSICION ENDLESS 1L LONG ISLAND 4X270  | G-155 | 20 ST/CS | 1000 ST/PAL | 92.59 ST/M2 | ST  | ST         | 0.77 KG/ST | 0.77 KG/ST   |
| 100153894 | L167012483 | ZOCALO ENDLESS 1L LONG ISLAND 8X220X1,5  | G-107 | 14 ST/CS | 560 ST/PAL  | 5.68 ST/M2  | ST  | ST         | 1.8 KG/ST  | 1.86 KG/ST   |