

**PLAYSTEEL 58**

**58.5017.8**

External part for wall-mounted built-in shower mixer with two-way diverter.


**FirUnico®**  
The Box 5.0

Article foreseeing FirUnico® universal  
built-in system


## Available finishings



Stainless Steel  
Art. 58.5017.8.50.00




Stainless Steel +  
Glacier White  
Corian®  
Art. 58.5017.8.50.20



Stainless Steel +  
Deep Nocturne  
Corian®  
Art. 58.5017.8.50.28

## Technical details



Item requiring a wall  
installation.



Item equipped with  
ceramic disc  
cartridge.  
0590576



Item equipped with  
diverter cartridge.  
0590575



Item with two inlets  
and two outlets.



DVGW certified item.  
EN 817

## Complementary necessary articles



### Art. 0510000

FirUnico® universal built-in  
system.

## Optional complementary products



---

**Art. 0500380**

Extension kit for FirUnico®, 20 mm long.

## Useful information

### Cleaning

#### Articles in stainless steel

Fir Italia taps and shower heads in stainless steel AISI 316L ensure long lasting durability. However, products are subjected to constant stress with daily use and therefore daily care and specific treatments are essential to preserve the beauty of steel surfaces. In particular, we strongly recommend drying any drops or water build-ups on the product thoroughly with a soft cloth.

Do not leave wet cloths or sponges on steel to prevent the formation of unsightly water stains. Do not leave iron tools in contact with steel surfaces, as doing so may cause corrosion by contact. Do not use abrasive sponges or steel wool that may scratch surfaces. Never for any reason use detergents containing chlorine or its compounds (bleach, muriatic acid, descaling solvent, etc.) as doing so could corrode the composition of steel, irreparably staining or oxidising surface. It is generally best not to leave opened packets or bottles of detergent or other chemical acid composition products in the vicinity of steel taps: the fumes may in some cases oxidise and corrode the steel.

### Maintenance

We recommend their frequent use (at least once every 5 days), to prevent the formation of limestone. A very sporadic use, in fact, favors limestone sedimentation, and the subsequent occurrence of malfunctions and abnormal water spurts.

### Installation

We recommend that you check the hardness of the water, as well as the condition of the hydraulic systems: if the percentage of limestone presence were to be particularly high, we recommend the installation of a sand filter and/or poly-phosphate filter (water softening system). In the same manner, in case of iron pipes or extremely dated ones and in bad conditions, we recommend, where possible, the replacement of the very system: the pipes, in fact, could release iron slag, which would corrode and jeopardize operation of the internal components of the articles. In such cases, as illustrated in the specific section, the warranty expires.

Trademarks, images, technical drawings, texts and further contents of this document are of FIR Italia S.p.A. exclusive property and are protected by copyright and by trademark right. Fraudulent reproduction, further elaboration or further uses with electronic media, for private or commercial utilization are, without preventive FIR Italia S.p.A. authorization, expressly forbidden.

## **Fir Italia S.p.A.**

Via Borgomanero, 6 - 28010 Vaprio D'Agogna (NO) Italy  
Ph. +39 0321 99.64.23 - Fax +39 0321 99.64.26 - [info@fir-italia.it](mailto:info@fir-italia.it)

