

Model: LINKFLOOR EMPIRE LIGHT GREY

Codes: 100203334 - L165003957


Group: G-230

Format: 22,86X180

Thickness: 7.5 mm



### COMPOSITION



	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	capa decorativa vinílica
Layer 3	0.9	Elastic PVC	Intermediate comfort layer
Layer 4	4.5	WPC	Cuerpo del material compuesto de WPC
Layer 5	EVA	1.5	Placa base de goma EVA

### CERTIFICATIONS

Floorscore certification

FLOORSCORE

### ADDITIONAL NOTES

In installations with underfloor heating the temperature must not exceed 27°

### FEATURES



Texture similar to brushed wood



Water-and-moisture resistant, suitable for wet areas such as bathrooms and kitchens



5 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.



Floor capable of dissipating excess electrical charges and distribute them over its entire surface



Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together



15 year home use warranty valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use category in accordance with ISO 10582.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.

### LABORATORY TESTS

Abrasion resistance	≤0.015g/1000 circles	EN 660-1:99*
Acoustic insulation	IICc=56 dB ; ΔIICc=28 dB ; STC=51 dB	ASTM E2179-08 ; ASTM E989-12*
Castor chair effect	No damage %	
Commercial area class	33	
Dynamic coefficient of friction	Clase DS	ANSI 137.1*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Fire resistance	Bfl-S1	EN13501-1*
Fungus test	1	ASTM G21:96*
Furniture leg effect	≤0.015 g/1000 ciclos	EN 424*
Heat resistance	0.064 M2*K/W	EN 12664*
Impact resistance	No damage KGF/MM2	
Private area class	23	
Residual footprint	Average=0.08 mm ; max=0.092 mm	ISO 24343-1*
Slip resistance (cls)	17 (Clase 1)	UNE-ENV 12633*
Slip resistance (r)	R-10	DIN 51130*
Swelling in thickness	±0.2 MM	ISO 24336*
Tensile strength of joints	Longitudinal: F0.2=2.35 kN/m; Transversal: F0.2=1.90 kN/m	ISO 24334*

### PACKING

Base unit	PIECES	
Boxes	1.6459 M2/BOX	
Gross weight	8.2993 KG/M2	
Net weight	8.0198 KG/M2	
Pallets	105.3389 M2/PAL	
Sale unit	M2	
Square meters	1 M2	
Units	0.4115 M2/PIECE	

### SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100241491	L167013089	MAMPER LINKFLOOR EMPIRE LIGHT GREY 120X7	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100211800	L167012922	PERFIL ADH LINKFLOOR EMPIRE LIGHTGREY3,5	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.77 KG/ST	0.8 KG/ST
100211747	L167012923	ZOCALO LINKFLOOR EMPIRE LIGHT GREY 8X220	G-121	14 ST/CS	560 ST/PAL	5.68 ST/M2	ST	ST	1.33 KG/ST	1.38 KG/ST

