Model: RANGE 1L ALSACIA Codes: 100226647 Group: G-270 Format: 22X220X1,5

L'ANTIC COLONIAL



ADDITIONAL NOTES

Although the tone of the skirtings, profiles and rungs of steps can vary, depending on the model, the color will be as similar as possible to the wooden floor. Due to better usage of the wood, any order of this reference may contain mean percentage tables of between 20% and 25%.

| COMPOSITION | | | | | | | | |
|-------------|---------|-------------|--------------------|-------------------|--|--|--|--|
| | | Size | Material | Type of material | | | | |
| | Layer 1 | 0.060-0.070 | Oil | Natur treatment | | | | |
| | Layer 2 | 4 | Hardwood Layer | | | | | |
| | Layer 3 | 9 | Intermediate Layer | Wood or HDF slats | | | | |
| | Layer 4 | 2 | Backside | Coniferous wood | | | | |

| LABORATORY TESTS | | | | | | | | |
|-------------------------|--------------|-------------------------------|--|--|--|--|--|--|
| Thermal conductivity | 0.13 W/M*°K | UNE-EN 12667:2002* | | | | | | |
| Heat resistance | 0.11 M2*°K/W | UNE-EN 12667:2002* | | | | | | |
| Formaldehyde emissions | E1 | EN 717* | | | | | | |
| Moisture content | 8.00% | UNE-EN 13183-1/AC:2004* | | | | | | |
| Flammability | Dfl-s1 | EN 13501* | | | | | | |
| Bulk density | 740 Kg/m3 | UNE-EN 323:1994* | | | | | | |
| Slip resistance | 45/63 | UNE-CEN/TS 15676:2008* | | | | | | |
| Biological durability | Clase 1 | UNE EN 335 -1 ; UNE EN 335-2* | | | | | | |
| Critical radiant flux | Clase 1 | ASTM E 648* | | | | | | |
| Smoke density (burning) | <450 Dmc | ASTM E 662* | | | | | | |



L'ANTIC COLONIAL

100226647 RANGE 1L ALSACIA

| FEATURES | | | | | | | | |
|--|---------------|------|--|--|--|--|--|--|
| This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation. | | | The finish imitates traditional hand brushing of the wood, providing a rough and artisan look as the one cabinetmakers would achieve in the past. | | | | | |
| Slight smoothing of the wood using a brush to achieve a surface with a slight relief. | | | Applying a color oil or varnish on the wood surface in order to get different color ranges. | | | | | |
| Beveled cut on all 4 edges of the board for emphasizing size | | | Combination of oils and waxes prepared for drying with UV lamps. With this finish, wood preserves the natural look of conventional oil but is more resistant to stains from everyday-use products and needs less maintenance. Advantages: Very natural look, low maintenance, and greater resistance to stains from water, wine, juice Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L. | | | | | |
| 30 Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial. | | | Is suitable for installing on water radiant heating | | | | | |
| \bigotimes Format where only one board has been used to finish the entire base surface | | | Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty. | | | | | |
| Number of the plane of the plan | | | It is necessary to apply adhesive for installing it. | | | | | |
| OAK Made with oak wood. | | | There are considerable color changes between pieces. | | | | | |
| Material from a European country. | | | Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability. | | | | | |
| 4 mm | | | | | | | | |
| | PAC | KING | | | | | | |
| Boxes | 2.904 M2/BOX | | | | | | | |
| Pallets | 69.696 M2/PAL | | | | | | | |
| Square meters | 1 M2 | | | | | | | |
| Sale unit | M2 | | | | | | | |
| Base unit | ST | | | | | | | |
| Net weight | 9.9649 KG/M2 | | | | | | | |
| Gross weight | 10.6612 KG/M2 | | | | | | | |
| | SDECIAL | | | | | | | |

| | SPECIAL PIECES | | | | | | | | | | |
|-----------|--------------------------------------|-------|---------------|-----------------|----------------|-----|------------|----------------|----------------|--|--|
| SAP | Description | Group | Boxes | Pallet | Units | SKU | Basic Unit | Net Weight | Gross weight | | |
| 100228864 | IGUALACION RANGE ALSACIA 4,5X270X1,3 | G-161 | 10 PIECES/BOX | 1000 PIECES/PAL | 8.23 PIECES/M2 | - | - | 1 KG/PIECES | 1.02 KG/PIECES | | |
| 100228886 | MAMPERLAN RANGE ALSACIA 7X120X3 | G-163 | 2 PIECES/BOX | 200 PIECES/PAL | 11.9 PIECES/M2 | - | - | 1.58 KG/PIECES | 1.64 KG/PIECES | | |
| 100228866 | TRANSICION RANGE ALSACIA 4X270X1,3 | G-161 | 10 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | - | - | 1 KG/PIECES | 1.02 KG/PIECES | | |
| 100228834 | ZOCALO RANGE ALSACIA 8X220X1,4 | G-128 | 12 PIECES/BOX | 600 PIECES/PAL | 5.68 PIECES/M2 | - | - | 2.58 KG/PIECES | 2.6 KG/PIECES | | |



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.