Curvature

Model: TORTONA 1L PALAZZO Codes: 100238602 Group: G-242 Format: 120X14,5X1,4



## ADDITIONAL NOTES

This material can show some pieces with whitening. Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 10% and 15%.

COMPOSITION									
		Size	Material	Type of material					
	Layer 1	0.060-0.070	Varnish	Apresto Mate treatment					
	Layer 2	3	Hardwood Layer						
	Layer 3	9	Intermediate Layer	Wood or HDF slats					
	Layer 4	2	Backside	Coniferous wood					

## TOLERANCES

0.1% of length.

LABORATORY TESTS Resistance to abrasion ≥500 UNE-EN 13696:2009\* 10.95 KG/M2 EN 14342\* Mass per surface Thermal conductivity 0.18 W/M\*°K UNE-EN 12667:2002\* 0.08 M2\*°K/W UNE-EN 12667:2002\* Heat resistance Formaldehyde emissions E1 EN 717\* 7.00% UNE-EN 13183-1/AC:2004\* Moisture content Dfl-s1 EN 13501\* Flammability Bulk density 782 Kg/m3 UNE-EN 323:1994\* Slip resistance Clase 2 (35/45) UNE-CEN/TS 15676:2008\* Biological durability Clase 1 UNE EN 335 -1 ; UNE EN 335-2\*



## 100238602 TORTONA 1L PALAZZO

## L'ANTIC COLONIAL

FEATURES									
F	Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.			Applying a color oil or varnish on the wood surface in order to get different or ranges.					
۲	Slight smoothing of the wood using a brush to achie relief.	eve a surface with a slight	$\bigcirc$	Beveled cut on the long sides of the board in order to create a continuity effect					
AM	L'ANTIC COLONIAL's varnishing, in two finishes, APR MATE (matte), provides a unique surface quality tha demanding requirements. Advantages: It achieves t because, since the pores are sealed, dirt and dust re be easily cleaned.	at satisfies the most he highest cleanliness	30	30 Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.					
Ð	Is suitable for installing on water radiant heating		$\bigcirc$	ightarrow Format where only one board has been used to finish the entire base surface					
$\bigcirc$	Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.			It is necessary to apply adhesive for installing it.					
0	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.			Made with oak wood.					
	There are consistent color changes between pieces.			Material from a European country.					
T	Material from a North American country.			PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests					
	3 mm								
PACKING									
Boxes		1.218 M2/BOX							
Pallets		34.104 M2/PAL							
Squar	Square meters 1 M2								
Sale unit M2		M2							
Base u	init	ST							
Net w	Net weight 12.2816 KG								
Gross	weight	12.931 KG/M2							

SPECIAL PIECES											
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100153232	IGUALACION TORTONA PALAZZO 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100176605	MAMPERLAN TORTONA 1L PALAZZO 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES		
100153236	TRANSICION TORTONA PALAZZO 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100153240	ZOCALO TORTONA PALAZZO 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES		



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.