



OAK TUFT

Oak Tuft features a 1-strip design and matt finish. Apperance is rustic, with knots and color variations from light to dark.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES	
Article Number	13106AEK1BKW185	Wood Species	Oak	TestMoistureContent	7%±2%
EANCode	7393969043229	Board	1-strip	TestMinimunMeanDensity	>500 kg/m³
Surface treatment	Matt lacquer	Grading	Lively	TestReactionToFire	Dfl-s1
Design features	Microbevelled 4-sided, Brushed	Range	Kährs Avanti	TestFormaldehydeEmission	E1
		Collection	Canvas Collection	TestContentPCP	≤ 5 x 10-6n
Dimensions	1860 x 127 x 13 mm	Resandable	2-3 times	TestBreakingStrength	NPD
Weight per Package x	12.69 kg	Natural/Stained	Stained	TestThermalConductivity	0,08 W/mK
Area per Package x	1.65 m ²	Brinell Value	3,7	TestThermalResistanceRValue	.15 (m2K/W)
AreaPerPalletM2	104.1	Joint	Woodloc® 5G	TestBiologDurability	Class 1
Package info	Packages may contain start and stop boards.	Floor heating	Yes	TestCarb2	Compliant
		Warranty	25 years		
DETAIL DESCRIPTION Wear-layer ma		Wear-layer material	Hardwood		
allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in		Wear-layer thickness	3 mm		
		Core material	Pine/Spruce lamella		
		Thickness	13 mm		

COLOUR CHANGE

Stained product - noticeable color change over time.

CERTIFICATES

((

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.