


Model: LINKFLOOR LEGEND LIGHT GREY

Codes: 100246150 - L167013235


Group: G-227

Format: 22,8X180

Thickness: 5.5 mm



COMPOSITION











	Size	Material	Type of material
Layer 1	0.5	Wear layer	Use layer with PU protection
Layer 2	0.1	Vinyl	decorative film
Layer 3	0.7	Elastic PVC	Intermediate comfort layer
Layer 4	3.2	SPC	SPC composite body
Layer 5	IXPE	1	IXPE motherboard

CERTIFICATIONS

Floorscore certification	FLOORSCORE
--------------------------	------------

FEATURES

-  Imitates the surface of wood
-  Water-and-moisture resistant, suitable for wet areas such as bathrooms and kitchens
-  10 year warranty for commercial use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  25 year warranty for domestic use valid for vinyl materials that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with ISO 10582.
-  Is suitable for installing on water radiant heating
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.

DIMENSIONAL FEATURES

Squareness of the item (q)	0.07 %	ASTM F2199*
Straightness of face	0.13 %	ASTM F2199*



LABORATORY TESTS

Abrasion resistance	CLASE T	
Acoustic insulation	IIC=51dB ; STC=54 dB	ASTM E492 ; ASTM E90*
Castor chair effect	No damage	
Commercial area class	33	EN 10582*
Dynamic coefficient of friction	Clase DS	ANSI 137.1*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*
Fire resistance	Bfl-S1	EN 13501*
Flexibility	PASS %	EN 435*
Formaldehyde emissions	E1	EN 717-2*
Heat resistance	0.052 M2**K/W	EN 12667*
Impact resistance	PASS	EN 433*
Private area class	23	EN 10582*
Resistance to chemicals	PASS	ASTM F925*
Slip resistance (cls)	Húmedo: Clase 2/Seco: Clase 3	UNE-ENV 12633*
Slip resistance (r)	R-10	DIN 51130*
Thermal conductivity	0.108 W/M**K	EN 12667*
Uv light fastness	>Grado 6	ISO 105-B02*

PACKING

Base unit	PIECES	
Boxes	2.4624 M2/BOX	
Gross weight	10.3631 KG/M2	
Net weight	10.0122 KG/M2	
Pallets	137.8944 M2/PAL	
Sale unit	M2	
Square meters	1 M2	
Units	0.4104 M2/PIECE	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100174756	L167012669	ESP. PERF ADH LINKFLOOR ALUMINIO 3,5X270	G-121	10 ST/CS	1000 ST/PAL	10.58 ST/M2	ST	ST	0.37 KG/ST	0.39 KG/ST
100264808	L167013375	MAMPER LINKFLOOR LEGEND LIGHT GREY 120X7	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100128267	L167901793	ZOCALO ALUMINIO 8X225	G-121	12 ST/CS	696 ST/PAL	5.56 ST/M2	ST	ST	1.57 KG/ST	1.62 KG/ST