


Model: ADVANCE 1L NATURAL  
Codes: 100065917 - L160241051  
Group: G-240  
Format: 18X220X1,1  
Thickness: 11 mm



### ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage tables of between 15% y 20%. While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

### COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	Apresto Mate treatment
Layer 2	2.5	Hardwood Layer	Madera de Roble
Layer 3	6.5	Intermediate Layer	Wood or HDF slats
Layer 4	2	Backside	Coniferous wood



















### TOLERANCES

Length of face	2200 MM
Width of face	180 MM

### LABORATORY TESTS

Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*
Bulk density	740 Kg/m3	UNE-EN 323:1994*
Critical radiant flux	Clase 1	ASTM E 648*
Flammability	Dfl-s1	EN 13501*
Formaldehyde emissions	E1	EN 717*
Gluing resistance	≥D3	EN 204*
Heat resistance	0.063 M2**K/W	UNE-EN 12667:2002*
Mass per surface	8.99 KG/M2	EN 14342*
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*
Resistance to abrasion	2000	UNE-EN 13696:2009*
Resistance to chair castors	PASS	EN 425*
Slip resistance	25/47	UNE-CEN/TS 15676:2008*
Smoke density (burning)	<450 Dmc	ASTM E 662*
Thermal conductivity	0.17 W/M**K	UNE-EN 12667:2002*

## FEATURES

-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
-  L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.
-  Is suitable for installing on water radiant heating
-  Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
-  It is necessary to apply adhesive for installing it.
-  There are consistent color changes between pieces.
-  Material from a North American country.
-  Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.
-  Applying a color oil or varnish on the wood surface in order to get different color ranges.
-  Beveled cut on the long sides of the board in order to create a continuity effect
-  Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
-  Format where only one board has been used to finish the entire base surface
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  Made with oak wood.
-  Material from a European country.
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  Noble layer

## PACKING

Base unit	PIECES
Boxes	2.376 M2/BOX
Gross weight	10.404 KG/M2
Net weight	9.7677 KG/M2
Pallets	76.032 M2/PAL
Sale unit	M2
Square meters	1 M2

## SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100112800	L165002489	IGUALACION ADVANCE NATURAL 4,5X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100176538	L165003618	MAMPERLAN ADVANCE 1L NATURAL 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100112806	L165002494	TRANSICION ADVANCE NATURAL 4X270X1,3	G-161	10 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	1 KG/ST	1.02 KG/ST
100112799	L165002491	ZOCALO ADVANCE NATURAL 8X220X1,4	G-128	12 ST/CS	600 ST/PAL	5.68 ST/M2	ST	ST	1.33 KG/ST	1.38 KG/ST

