

Model: AUTHENTIC 1L PURE

Codes: 100171983

Group: G-265


Format: 24X220X1,35



ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 20% y 25%.

COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Oil	Natur Plus treatment
Layer 2	3.5	Hardwood Layer	
Layer 3	10	Intermediate Layer	Softwood veneer

LABORATORY TESTS

Mass per surface	7.41 KG/M2	EN 14342*
Thermal conductivity	0.133 W/M**K	UNE-EN 12667:2002*
Heat resistance	0.09 M2**K/W	UNE-EN 12667:2002*
Formaldehyde emissions	E1	EN 717*
Gluings resistance	≥D3	DIN EN 204*
Resistance to chair castors	No damage	DIN EN 425*
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*
Flammability	Dfl-s1	EN 13501*



FEATURES

- It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly
- Applying a color oil or varnish on the wood surface in order to get different color ranges.
- Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
- Beveled cut on all 4 edges of the board for emphasizing size
- Combination of oils and natural waxes with air drying that leave the wood with open pores. This type of oil penetrates into the wood continuously, even when it is fitted, so that it may have a 'dry' look when opened to be installed.
Advantages: Easy repair of dents and scratches, very natural look, and easy maintenance with the right products. Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.
- Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
- Is suitable for installing on water radiant heating
- Format where only one board has been used to finish the entire base surface
- Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
- It is necessary to apply adhesive for installing it.
- Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
- Made with oak wood.
- There are consistent color changes between pieces.
- Material from a North American country.
- Material from a European country.
- PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
- Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.
- 3.5 mm

PACKING

Boxes	3.168 M2/BOX
Pallets	104.544 M2/PAL
Square meters	1 M2
Sale unit	M2
Base unit	ST
Net weight	7.8636 KG/M2
Gross weight	8.3277 KG/M2

SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100229370	IGUALACION AUTHENTIC PURE 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100176731	MAMPERLAN AUTHENTIC 1L PURE 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100229380	TRANSICION AUTHENTIC PURE 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100177641	ZOCALO AUTHENTIC PURE 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	2.58 KG/PIECES	2.6 KG/PIECES

