## L'ANTIC COLONIAL

Model: JAVA 1L COFFEE Codes: 100270764 Group: G-257 Format: 9X54X1,4



COMPOSITION					
		Size	Material	Type of material	
	Layer 1	0.060-0.070	Varnish	APRESTO MATTE	
	Layer 2	3	Hardwood Layer		
	Layer 3	9	Intermediate Layer		
	Layer 4	2	Backside		

	TOLERANCES	
Squareness of the item	0.2% of width.	

LABORATORY TESTS					
Thermal conductivity	0.108 W/M*ºK W/M*°K	UNE-EN 12667:2002**			
Formaldehyde emissions	Clase E1	EN-717/1:2006**			
Flammability	Dfl-S1	UNE EN 13501-1:2007**			
Slip resistance	USRV 15				
Biological durability	Clase 2				

## **FEATURES**



This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



It is necessary to apply adhesive for installing it.



Made with oak wood.



There are considerable color changes between pieces.



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.







1/2

It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

IAVA 11 COFFEE

## L'ANTIC COLONIAL

PACKING					
Boxes	0.583 M2/BOX				
Pallets	51.3036 M2/PAL				
Square meters	1 M2				
Sale unit	M2				
Base unit	ST				
Net weight	10.0447 KG/M2				
Gross weight	10.4769 KG/M2				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

16/06/2022