Model: JAVA 1L GREY Codes: 100270880 Group: G-257 Format: 9X54X1,4

L'ANTIC COLONIAL



	C	OMPOSITION	
	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	APRESTO MATTE
Layer 2	3	Hardwood Layer	
Layer 3	9	Intermediate Layer	
Layer 4	2	Backside	
		OLERANCES	

Squareness of the item

	LABORATORY TESTS	
Thermal conductivity	0.108 W/M*ºK W/M*°K	UNE-EN 12667:2002**
Formaldehyde emissions	Clase E1	EN-717/1:2006**
Flammability	Dfl-S1	UNE EN 13501-1:2007**
Slip resistance	USRV 15	
Biological durability	Clase 2	

0.2% of width.

FEATURES Applying a color oil or varnish on the wood surface in order to get different color ranges. This installation system consists in assembling the boards with slots and cuts on their edges by applying a slight pressure on the boards. The boards are then bonded with white glue. Tools are needed for the installation. Â Slight smoothing of the wood using a brush to achieve a surface with a slight relief. (H)Beveled cut on all 4 edges of the board for emphasizing size L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned. Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial. (30) Is suitable for installing on water radiant heating Format where only one board has been used to finish the entire base surface ()Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty. S It is necessary to apply adhesive for installing it. (оак) Made with oak wood. There are considerable color changes between pieces. Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability. 3 mm B



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

L'ANTIC COLONIAL

100270880 JAVA 1L GREY

	PACKING
Boxes	0.583 M2/BOX
Pallets	51.3036 M2/PAL
Square meters	1 M2
Sale unit	M2
Base unit	ST
Net weight	10.1888 KG/M2
Gross weight	10.621 KG/M2



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.