Model: LUTIER 1L GREY Codes: 100272991 Group: G-235 Format: 18X220X1,4

## L'ANTIC COLONIAL



COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Varnish	APRESTO MATTE			
	Layer 2	2.5	Hardwood Layer				
	Layer 3	9	Intermediate Layer	PINE			
	Layer 4	2.5	Backside	PINE			
TOLERANCES							

	I O ELIV (INCES			
Squareness of the item	0.2% of width.			
Curvature	0.1% of length.			
Notice Notice   CABORATORY TESTS CABORATORY TESTS   Imal conductivity 0.14 W/M*ºK W/M*ºK UNE-EN 12667:2002**   It resistance 0.103 M2*ºK/W M2*°K/W UNE-EN 12667:2002**   Inaddehyde emissions 0.011 ±0.001 mg/m3 EN-717/1:2006**   Imability Dfl-S1 UNE EN 13501-1:2007**				
Thermal conductivity	0.14 W/M*ºK W/M*°K	UNE-EN 12667:2002**		
Heat resistance	0.103 M2*ºK/W M2*°K/W	UNE-EN 12667:2002**		
Formaldehyde emissions	0.011 ±0.001 mg/m3	EN-717/1:2006**		
Flammability	Dfl-S1	UNE EN 13501-1:2007**		
Bulk density	min 500Kg/m3	UNE-EN 323:1994**		
Slip resistance	Clase 2 (35/45)	UNE-CENT/TS 15676:2008**		



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

## L'ANTIC COLONIAL

	FEAT	URES	5				
It is one of the easiest to install and safest systems in the market. We just need to adjust the board to be installed longitudinally to the one already placed, by applying a soft pressure without the need for any type of tool. Both pieces will fit and will be secured thanks to the safety tab. It is just as simple to take apart, which makes for a quick disassembly			Applying a color oil or varnish on the wood surface in order to get different c ranges.				
L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.			Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.				
Is suitable for installing on water radiant heating		$\bigcirc$	Format where only one board has been used to finish the entire base surface				
Material with some knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.			Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.				
It is necessary to apply adhesive for installing it.			There are considerable color changes between pieces.				
Material from a European country.		Ç, FSC	Independent (non-governmental) certificate that guarantees consumers that forest products come from rationally exploited forests				
Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.			2.5 mm				
	PAC	king					
Boxes	2.772 M2/BOX						
Pallets	110.88 M2/PAL						
Square meters	1 M2						
Sale unit	M2						
Base unit	ST						
Net weight	8.3737 KG/M2						
Gross weight	8.8106 KG/M2						

	SPECIAL PIECES										
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight		
100272965	IGUALACION LUTIER GREY 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100272994	MAMPERLAN LUTIER 1L GREY 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES		
100272937	TRANSICION LUTIER GREY 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES		
100272955	ZOCALO LUTIER GREY 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES		



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.