Model: RANGE 1L NORMANDIA Codes: 100226684 Group: G-270 Format: 22X220X1,5



ADDITIONAL NOTES

Although the tone of the skirtings, profiles and rungs of steps can vary, depending on the model, the color will be as similar as possible to the wooden floor. Due to better usage of the wood, any order of this reference may contain mean percentage tables of between 20% and 25%.

COMPOSITION							
		Size	Material	Type of material			
	Layer 1	0.060-0.070	Oil	Natur treatment			
	Layer 2	4	Hardwood Layer				
	Layer 3	9	Intermediate Layer	Wood or HDF slats			
	Layer 4	2	Backside	Coniferous wood			

LABORATORY TESTS							
Thermal conductivity	0.13 W/M*°K	UNE-EN 12667:2002*					
Heat resistance	0.11 M2*°K/W	UNE-EN 12667:2002*					
Formaldehyde emissions	E1	EN 717*					
Moisture content	8.00%	UNE-EN 13183-1/AC:2004*					
Flammability	Dfl-s1	EN 13501*					
Bulk density	740 Kg/m3	UNE-EN 323:1994*					
Slip resistance	45/63	UNE-CEN/TS 15676:2008*					
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*					
Critical radiant flux	Clase 1	ASTM E 648*					
Smoke density (burning)	<450 Dmc	ASTM E 662*					



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

L'ANTIC COLONIAL

100226684 RANGE 1L NORMANDIA

	FEATURE	S				
This installation system consists in assembling the boards with slo their edges by applying a slight pressure on the boards. The board bonded with white glue. Tools are needed for the installation.		The finish imitates traditional hand brushing of the wood, providing a rough a artisan look as the one cabinetmakers would achieve in the past.				
Slight smoothing of the wood using a brush to achieve a surface v relief.	with a slight 🛛 🔗	Applying a color oil or varnish on the wood surface in order to get different color ranges.				
Beveled cut on all 4 edges of the board for emphasizing size	N	Combination of oils and waxes prepared for drying with UV lamps. With this finish, wood preserves the natural look of conventional oil but is more resistant to stains from everyday-use products and needs less maintenance. Advantages: Very natural look, low maintenance, and greater resistance to stains from water wine, juice Right after installing and before its first use we recommend the use of CLEAN&GREEN AQUA OIL 1 L.				
30 Quality product made with selected raw materials, guaranteeing residential use for 30 years as provided by L' Antic Colonial.	its full	Is suitable for installing on water radiant heating				
Format where only one board has been used to finish the entire b	base surface	Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.				
It is necessary to apply adhesive for installing it.	$\mathbf{\hat{o}}$	Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.				
OAK Made with oak wood.	8	There are considerable color changes between pieces.				
Material from a European country.	۲	Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.				
4 mm						
	PACKING					
Boxes 2.904 M2/B						
Pallets 69.696 M2/I						
Square meters 1 M2						
Sale unit M2						
Base unit ST						
Net weight 9.9525 KG/M	M2					
Gross weight 10.6488 KG/	/M2					
	SPECIAL PIE					

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100228837	IGUALACION RANGE NORMANDIA 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100228897	MAMPERLAN RANGE NORMANDIA 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100228876	TRANSICION RANGE NORMANDIA 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100228836	ZOCALO RANGE NORMANDIA 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	2.58 KG/PIECES	2.6 KG/PIECES



It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.