

Technical Datasheet



Kronoflooring GmbH Mühlbacher Straße 1 01561 Lampertswalde/Germany Tel. +49 3522 33 30 • Fax: +49 3522 33 399 info@krono-original.com

Direct Pressure Laminate
Level of use according to EN 13329: 23/32 - AC4







Heavy domestic use

Medium commercial use

The guarantee is valid for domestic use according to the conditions of guarantee*

DIMENSION

dimension	thickness (d)	8 ± 0,50 mm · dmax - dmin ≤ 0,50 mm		
	length	1285 ± 0,50 mm		
	width (b)	192 ± 0,10 mm · bmax - bmin ≤ 0,20 mm		
profile	long side	twin clic	short side	1clic2go pure
groove	long side	real groove	short side	real groove



TOI	ED	ANICE	•

TOLERANCE		
squareness	EN 13329	≤ 0,20 mm
straightness	EN 13329	≤ 0,30 mm
flatness crosswise	EN 13329	concave: ≤ 0,15% · convex: ≤ 0,20%
flatness length	EN 13329	concave: ≤ 0,50% · convex: ≤ 1,00%
gaps between elements	EN 13329	average: ≤ 0,15 mm · max: ≤ 0,20 mm
height difference between elements	EN 13329	average: ≤ 0,10 mm · max: ≤ 0,15 mm
misalignment		± 2 mm

TEST

abrasion resistance		EN 13329	AC4 (≥ 4000 rpm)	
impact resistance		EN 13329	small ball ≥ 12 N · big ball ≥ 750 mm	
grou stain resistance	up 1 & 2	EN 13329	grade 5	
grou	up 3		≥ grade 4	
castor chair test		EN 13329	no change in appearance or damage, as defined per EN 425	
effect of a furniture leg		EN 13329	no damage shall be visible, when testet with foot type 0	
static indentation		EN 13329	≤ 0,05 mm	
light fastness		EN 13329	grey scale ≥ 4 at blue wool grade 6	
dimensional variations after cl relative humidity	changes in	EN 13329	lengthwise ≤ 0,9 mm · crosswise ≤ 0,9 mm	
locking strength		EN 13329	length ≥ 1 kN/m · width ≥ 2 kN/m	
surface soundness		EN 13329	≥ 1,25 N/mm²	

ENVIRONMENT

Formaldehydemission	EN 16516	class E1

PHYSICAL BEHAVIOR

PHYSICAL BEHAVIOR		
fire behavior	EN 13501-1	Cfl s1
slide resistance	EN 13893	technical class DS
thermal resistance	EN 12667	0,073 (m²K)/W ± 15%
thermal conductivity	EN 12664	0,110 W/(m*K) ± 15%

^{*}Detailed warranty conditions are available at www.krono-original.com

The data sheet is updated regularly to meet new technological standards. This version replaces all previous versions as well as those which are undated. This version takes effect upon creation. Version 02/2022