



## OAK KINDA

The earthen grey stain on this single-strip oak floor from the Småland Collection allows the warmer tones in the base to come through, resulting in a very rustic expression with a delicately balanced colour variation. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

### PRODUCT DETAILS

<b>Article Number</b>	151NDSEK02KW240
<b>EAN Code</b>	7393969039031
<b>Surface treatment</b>	Oil This floor should be oiled immediately after installation.
<b>Dimensions</b>	2420 x 187 x 15 mm
<b>Weight per Package (kg)</b>	22 kg
<b>Area per Package (m<sup>2</sup>)</b>	2.7 m <sup>2</sup>
<b>Area per pallet (m<sup>2</sup>)</b>	122.4 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

The colour matures over time.

### FACTS

<b>Design</b>	1-strip
<b>Grading</b>	Expressive
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Småland Collection
<b>Resandable</b>	2-4 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness (mm)</b>	15 mm
<b>Installation method</b>	Floating, Glue-down
<b>Surface Colour</b>	Earth Grey

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>	.11 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	


## Other products in this collection



Oak Klinta



Oak Kinda



Oak Sevede




Oak Ydre



Oak Möre




Oak Vista



Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeländ

## CERTIFICATES



## Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.