



## OAK CURIO

The charcoal-brown hues found in this single-strip oak floor from the Canvas Collection range from dark to light. Natural variations in the timber, alongside mottled knots and cracks, give it a rustic expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Four-sided bevelling at the edges ensures a classic full plank look and feel.

### PRODUCT DETAILS

<b>Article Number</b>	13106AEKA1KW185
<b>EAN Code</b>	7393969043915
<b>Surface treatment</b>	Matt lacquer
<b>Dimensions</b>	1860 x 127 x 13 mm
<b>Weight per Package (kg)</b>	12.687 kg
<b>Area per Package (m<sup>2</sup>)</b>	1.652 m <sup>2</sup>
<b>Area per pallet (m<sup>2</sup>)</b>	104.076 m <sup>2</sup>
<b>Package info</b>	Packages may contain start and stop boards.

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Design</b>	1-strip
<b>Grading</b>	Lively
<b>Range</b>	Kährs Avanti
<b>Collection</b>	Canvas Collection
<b>Resandable</b>	2-3 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3,7
<b>Joint</b>	Woodloc® 5G
<b>Floor heating</b>	Yes
<b>Warranty</b>	25 years
<b>Wear-layer material</b>	Hardwood
<b>Core material</b>	Pine/Spruce lamella
<b>Thickness (mm)</b>	13 mm
<b>Installation method</b>	Floating, Glue-down
<b>Surface Colour</b>	Dark brown

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>	>500 kg/m <sup>3</sup>	
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,08 W/mK
<b>Thermal Resistance R-Value</b>	.15 (m <sup>2</sup> K/W)	
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>	Compliant	

## Other products in this collection



Oak Fawn



Oak Henna




Oak Heather



Oak Cadence



Oak Reiter



Oak Muse




Oak Curio



Oak Carbon



Oak Etch



Oak Tuft



Oak Mostra

## CERTIFICATES



### Descriptions & Imagery

*All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.*