



ASH CORAL

Ash Coral has a modern yet classic look with tones of warm white corals from sandy beaches. The characteristics of the ash enhance the impression of this matt lacquered 3-strip floor.

PRODUCT DETAILS

| | |
|---|---|
| Article Number | 133B11AKLCKW226 |
| EAN Code | 7393969048392 |
| Surface treatment | Matt lacquer |
| Dimensions | 2266 x 188 x 13 mm |
| Weight per Package (kg) | 24.55 kg |
| Area per Package (m²) | 3.41 m ² |
| Area per pallet (m²) | 119.35 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

Any naturally occurring wood colour variations allowed, from light blond to dark brown. The product includes medium sized sound and black knots/fillings. Knots and fillings may vary in size and numbers.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|----------------------------|---------------------|
| Design | 3-strip |
| Grading | Lively |
| Range | Kährs Avanti |
| Collection | Ground Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 4,0 |
| Joint | Woodloc® 5G |
| Floor heating | Yes |
| Warranty | 20 years |
| Wear-layer material | Hardwood |
| Core material | Pine/Spruce lamella |
| Thickness (mm) | 13 mm |
| Installation method | Floating, Glue-down |
| LRV | 62 |

TECHNICAL PROPERTIES

| | | |
|--|--------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .09 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |

Other products in this collection




OAK CLAY



ASH CORAL



OAK SAND



OAK SEED



OAK CHALK

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.