L'ANTIC COLONIAL

Model: ADVANCE 1L ASH Codes: 100317043 Group: G-244

Format: 218X19,8X1,4CM



ADDITIONAL NOTES

Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 15% y 20%. While the color of the skirting boards, profiles, and step borders may vary depending on the model, the color shall be as similar as possible to the wood floor.

COMPOSITION						
		Size	Material	Type of material		
	Layer 1	0.060-0.070	Varnish	Apresto Mate treatment		
	Layer 2	3	Hardwood Layer	Oak wood		
	Layer 3	9	Intermediate Layer	Wood or HDF slats		
	Layer 4	2	Backside	Coniferous wood		

LABORATORY TESTS						
Resistance to abrasion	≥500	UNE-EN 13696*				
Thermal conductivity	0.17 W/M*K	UNE-EN 12667:2002*				
Heat resistance	0.082 M2*K/W	UNE-EN 12667:2002*				
Formaldehyde emissions	E1	EN 717*				
Gluing resistance	≥D3	EN 204*				
Moisture content	5-9 %	UNE-EN 13183-1/AC:2004*				
Flammability	Dfl-s1	EN 13501*				
Bulk density	785 KG/M3	UNE-EN 323:1994*				
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*				
Slip resistance (pendulum-wet)	CL 1 (30)	UNE 41901*				
Slip resistance (pendulum-dry)	CL 3 (50)	UNE 41902*				
Slip resistance (dcof)	0.43	ANSI A137.1*				





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

07/07/2023

ADVANCE 1L ASH

L'ANTIC COLONIAL

FEATURES



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



Slight smoothing of the wood using a brush to achieve a surface with a slight relief.



Applying a color oil or varnish on the wood surface in order to get different color ranges.



Beveled cut on all 4 edges of the board for emphasizing size



L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.



Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.



Is suitable for installing on water radiant heating



Format where only one board has been used to finish the entire base surface



Material with many knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.



Made with oak wood.



There are consistent color changes between pieces.



Material from a North American country.



Material from a European country.



PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests



Structure formed by an upper layer that shows the noble aspect of the material, an intermediate layer of wood of different typology, depending on the collection, or HDF board that compensates the tensions between the different parts and a lower plywood that provides dimensional stability.



3 mm



It is necessary to apply adhesive for installing it.



Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

PACKING					
Sales units per box	3.02148 M2/BOX				
Sales units per pallet	105.751799 M2/PAL				
Sales units per square meter	1 M2				
Sale unit	M2				
Base unit	ST				
Net weight	12.2579 KG/M2				
Gross weight	12.716616 KG/M2				

SPECIAL PIECES									
SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100317025	IGUALACION ADVANCE ASH 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100317050	MAMPERLAN ADVANCE 1L ASH 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100317028	TRANSICION ADVANCE ASH 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100317060	ZOCALO ADVANCE ASH 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES





It is advisable to follow the installation and maintenance instructions published by L'ANTIC COLONIAL, S.A.U., observing in any case the legal or regulatory requirements that may exist for each area of use. Do not use aggressive cleaning agents, such as acids, or metallic or sharp elements. In public places this material must comply with the slipperiness requirements of the Spanish Technical Building Code. This document is purely commercial and may not be used in any legal or administrative proceedings, neither as an expert opinion nor as documentary evidence, unless expressly authorized by L'ANTIC COLONIAL, S.A.U.

07/07/2023 2/2