


## 【Basic Parameters】

- Material: AL6063-T5, spraying surface
- Coating: Black (RAL9005)
- Size:  $\phi 42$ mm optional
- IP grade: IP20
- CCT: 2700/3000/3500/4000K optional
- CRI: 90
- SDCM: <3 Step (ANSI)
- Spotlight angle: 24°/36°
- Light efficiency: 66/83 lm/W
- Input voltage: DC48V
- Lighting direction: downward
- Dimming method: Non / DALI-2 / Tuya Bluetooth / CASAMBI
- Application: Indoor
- Certification: CE, UKCA, ROHS, Reach
- Warranty: 3 years




## 【Luminaire Parameters】

Version	Model	Size	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	M20S-42	42mm [0.14ft]	48VDC	0.13 [0.93A/ft]	6.0 [42.86W/ft]	6.6 [47.14W/ft]	>90	24°	2700K	365
									3000K	375
									3500K	385
									4000K	400
								36°	2700K	455
									3000K	470
									3500K	485
									4000K	500

Note:


1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

## [Optical Parameter]




Luminous intensity distribution diagram

24°




AAI Figure



Luminous intensity distribution diagram

36°



AAI Figure

## [Product mechanical data]

