


[Basic Parameters]

- Material: Silicone Neon
- Coating: Black
- Length: 1000mm/2500mm/5000mm optional
- IP grade: IP20
- CCT: 2700/3000/3500/4000K optional
- CRI: 90
- SDCM: <3 Step (ANSI)
- Light efficiency: 65 lm/W
- Input voltage: DC48V
- Lighting direction: 360° round
- Dimming method: Non / DALI-2 / Tuya Bluetooth / CASAMBI
- Application: Indoor
- Certification: CE、UKCA、 ROHS、Reach
- Warranty: 3 years



[Luminaire Parameters]

Version	Model	Length	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	M20NK-25	1000mm [3.28ft]	48VDC	0.30 [0.09A/ft]	14.0 [4.27W/ft]	15.4 [4.70W/ft]	>90	360°	2700K	830 [255LM/ft]
									3000K	845 [260LM/ft]
									3500K	870 [265LM/ft]
									4000K	910 [275LM/ft]
		2500mm [8.20ft]		2700K	2080 [255LM/ft]					
				3000K	2120 [260LM/ft]					
				3500K	2175 [265LM/ft]					
				4000K	2275 [275LM/ft]					
		5000mm [16.40ft]		2700K	4160 [255LM/ft]					
				3000K	4235 [260LM/ft]					
				3500K	4355 [265LM/ft]					
				4000K	4550 [275LM/ft]					

Note:

1. The output data is based on the testing result of Ra90,4000k luminaires;

2. The tolerance of output data can be vary up to 10%;

3. The output data is typical value.

[Product mechanical data]

